

AD-A215 282

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE Sep 29, 1982	3. REPORT TYPE AND DATES COVERED Final (30 Sep 81- 29 Sept 82)	
4. TITLE AND SUBTITLE BASIC INSTABILITY MECHANISMS IN CHEMICALLY REACTING SUBSONIC AND SUPERSONIC FLOWS			5. FUNDING NUMBERS 61102F 2308/A2	
6. AUTHOR(S) T.Y. Toong				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Massachusetts Institute of Technology Department of Mechanical Engineering Cambridge, MA 02139			8. PERFORMING ORGANIZATION REPORT NUMBER AFOSR-TR- 89 - 1608	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR BLDG 410 BAFB DC 20332-6448			10. SPONSORING / MONITORING AGENCY REPORT NUMBER AFOSR-78-3662	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Examination of low-frequency instability in ramjet dump combustors shows that the oscillations are triggered and sustained by interactions between non-uniform entropy zones and pressure waves. Pressure waves are produced as entropy waves convect through a choked nozzle and entropy waves are generated as the pressure waves perturb the combustion zone. A linearized stability theory is developed for the case of near blow-off which corresponds to maximum rumble. Both oscillation frequencies and amplification rates are obtained. The theory is used to analyze the effects of combustor configurations (including combustor-to-inlet area ratio, nozzle-to-combustor area ratio, combustor diameter, presence of flameholder and mode of fuel injection), inlet stagnation temperature, and fuel-air ratio on stability. Both predicted frequencies and stability characteristics agree well with the experimental observations. One possible mechanism of turbulence-combustion interactions has been examined by studying the development of Tollmien-Schlichting waves in a reacting shear layer. Analysis shows that the growth rates of these waves depend on the order, the thermicity, and the activation energy of the Arrhenius-type chemical				
14. SUBJECT TERMS			15. NUMBER OF PAGES 16	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	

reaction as well as the disturbance wavelengths and Damkohler's similarity parameters. Two papers have been published and two are in preparation.

AFONR-TR- 89-1608

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

ANNUAL TECHNICAL REPORT ON RESEARCH

SUPPORTED BY GRANT AFOSR-78-3662

(September 30, 1981-September 29, 1982)

Basic Instability Mechanisms
in Chemically Reacting Subsonic and Supersonic Flows

T. Y. Toong

Massachusetts Institute of Technology

Summary of Progress

Examination of low-frequency instability in ramjet dump combustors shows that the oscillations are triggered and sustained by interactions between non-uniform entropy zones and pressure waves. Pressure waves are produced as entropy waves convect through a choked nozzle and entropy waves are generated as the pressure waves perturb the combustion zone. A linearized stability theory is developed for the case of near blow-off which corresponds to maximum rumble. Both oscillation frequencies and amplification rates are obtained.

The theory is used to analyze the effects of combustor configurations (including combustor-to-inlet area ratio, nozzle-to-combustor area ratio, combustor diameter, presence of flameholder and mode of fuel injection), inlet stagnation temperature, and fuel-air ratio on stability. Both predicted frequencies and stability characteristics agree well with the experimental observations.

One possible mechanism of turbulence-combustion interactions has been

examined by studying the development of Tollmien-Schlichting waves in a reacting, shear layer. Analysis shows that the growth rates of these waves depend on the order, the thermicity, and the activation energy of the Arrhenius-type chemical reaction as well as the disturbance wavelengths and Damköhler's similarity parameters.

Two papers have been published and two are in preparation.

RELEVANCE TO USAF

This research on instability mechanisms involved in the mutual influence among sound, entropy, and vorticity modes in chemically reacting subsonic and supersonic flows will aid in the design and the development of advanced power and propulsion systems, in the alleviation of noise pollution, and in the effective control and prevention of explosions.

I. Objective and Scope of Work

The main objectives of this work are to determine the major mechanisms governing the efficiency, power output, stability, and pollutant emission of propulsion devices as well as safety against explosions. Two problems have been studied during the past grant period: (1) Triggering and sustenance of low-frequency instability in dump combustors and (2) temporal development of turbulence-combustion interactions. The following section summarizes briefly the results obtained.

II. Results and Discussion

(1) Triggering and Sustenance of Low-Frequency Instability in Dump Combustors

One major problem related to the use of dump combustors in propulsion devices is to eliminate the low-frequency oscillations. Figure 1a shows the configuration of a coaxial dump combustor, used in the facility of Aero Propulsion Laboratory, AF Wright Aeronautical Laboratories. Here, the flame is stabilized by the use of a flameholder or simply a recirculation zone. Figure 1b shows a transition from low-frequency instability at high equivalence ratio to high-frequency instability at lower equivalence ratio. Such a trend has been predicted by a theoretical analysis conducted during the past grant period.

The low-frequency instability is believed to be triggered and sustained

by interactions between non-uniform entropy zones and pressure waves. Figure 2, shows the generation of pressure waves as an entropy wave is convected through a choked nozzle and the generation of the entropy wave as the pressure waves interact with the combustion zone.

A linear perturbation analysis has been conducted to study the instability behavior. Figure 3 shows a comparison of the predicted frequencies with the observations obtained at the AF Aero Propulsion Laboratory for three combustor lengths and diameters with and without a flameholder. The general agreement is quite satisfactory.

The theory is also used to predict the effects of combustor configurations (including combustor-to-inlet area ratio, nozzle-to-combustor area ratio, combustor diameter, presence of a flameholder, and mode of fuel injection), inlet stagnation temperature, and fuel-air ratio on the amplification rates. Figure 4 shows the effect of combustor-to-inlet area ratio for wall injection at different fuel-air ratios together with the corresponding combustion efficiencies. As the combustor diameter increases for a given inlet area, the flow tends to be more stable with accompanying increase in the combustion efficiency. The amplification rates are smaller at lower fuel-air ratio, suggesting possible domination of high-frequency instability under such conditions as observed in the experiments (cf. Fig. 1b). The solid symbols in Fig. 4 indicate stable flows in the experiments. Note that the corresponding predictions show negative amplification or attenuation.

Similar trend is also observed for uniform injection. Theory also shows that the flow is more stable at higher inlet stagnation temperatures,

smaller nozzle-to-combustor area ratios (although the reverse trend is also predicted for some conditions), larger combustor diameters, and with a flameholder. These findings are found to be in qualitative agreement with the APL observations.

(2) Temporal Development of Turbulence-Combustion Interactions

One possible mechanism of turbulence-combustion interactions has been examined by studying the growth of Tollmien-Schlichting disturbance waves in a reacting shear layer. It is known that non-reacting, inviscid, shear layers are always unstable to normal-mode disturbances when the mean velocity profile has an inflection point. Figure 5 shows schematically the development of instability in such a flow where vortices are formed due to the growth of the disturbance waves.

Analysis shows that the growth rates of these waves depend on the order, the thermicity, and the activation energy of the Arrhenius-type chemical reaction as well as the disturbance wavelengths and Damköhler's similarity parameters. In the case of quasi-steady situation, the chemical effect is represented by the product of Damköhler's third similarity parameter and the non-dimensional activation energy. Figure 6 shows this effect of the activation energy on the growth rates for different wavelengths. The chemical effect is smaller for smaller α^* or longer wavelength. In other words, the chemical kinetics has different effects on eddies of different sizes. Regardless of the wavelengths, however, one observes in general that exothermic reaction increases the growth rates.

III. Publications and Reports


See attached Enclosure I.

IV. Professional Personnel

Professor T. Y. Toong and Dr. G. E. Abouseif.


CAPTION TO FIGURES

- Figure 1 (a) A typical coaxial dump combustor
(b) Transition from low-frequency instability to high-frequency instability resulting from a decrease in equivalence ratio
- Figure 2 Illustrating low-frequency instability mechanism
- Figure 3 Comparison between predicted and observed frequencies for low-frequency instability; three combustor lengths and diameters with and without a flameholder
- Figure 4 Effects of combustor-to-inlet area ratio on amplification rate and combustion efficiency for wall injection at different fuel-air ratios
- Figure 5 Development of instability in a shear flow showing the formation of vortices due to the growth of Tollmien-Schlichting disturbance waves
- Figure 6 Effects of activation energy on growth rates of disturbance waves of different wavelengths



CONFIGURATION OF A TYPICAL COAXIAL DUMP COMBUSTOR

(a)




TRANSITION FROM THE LOW-FREQUENCY INSTABILITY TO THE HIGH-FREQUENCY INSTABILITY RESULTING FROM A DECREASE IN EQUIVALENCE RATIO

(b)

Figure 1

FIG. 2a GENERATION OF PRESSURE WAVES BY CONVECTION OF ENTROPY WAVES THROUGH A CHOKED NOZZLE

FIG. 2b GENERATION OF ENTROPY WAVES BY PRESSURE WAVES INCIDENT ON COMBUSTION ZONE






Figure 3





Figure 4





Figure 5



EFFECTS OF ACTIVATION ENERGY ON GROWTH RATES OF DISTURBANCE WAVES AT DIFFERENT WAVE NUMBERS

Figure 6

ENCLOSURE I

Basic Instability Mechanisms
in Chemically Reacting Subsonic and Supersonic Flows

Publications and Reports

(Grants AFOSR-74-2619 and AFOSR-78-3662)

1. Toong, T. Y., "Chemical Effects on Sound Propagation", Combustion and Flame, Vol. 18, pp. 207-216, 1972.
2. Arbeau, P. A., "A Theoretical Study on Generation of Vorticity due to Chemical Reaction", S.M. Thesis, Department of Mechanical Engineering, M.I.T., June 1972.
3. Williams, P. C., "Experiments on Sound Propagating in a Reacting Hydrogen-Chlorine Mixture", Research Report, Combustion and Propulsion Laboratory, Department of Mechanical Engineering, M.I.T., January 1973.
4. Toong, T. Y., "Instabilities in Reacting Flows", invited for presentation at the Fourth International Colloquium on Gasdynamics of Explosions and Reactive Systems, University of California at San Diego, La Jolla, Calif., July 10, 1973; Acta Astronautica, 1, pp. 317-344, 1974.
5. Toong, T. Y., "Basic Instability Mechanisms in Chemically Reacting Subsonic and Supersonic Flows", U.S. Air Force Office of Scientific Research, Final Scientific Report, No. AFOSR-TR-74-0065, November 1973.

6. Toong, T. Y., Arbeau, P., Garris, C. A. and Patureau, J.-P., "Acoustic-Kinetic Interactions in an Irreversibly Reacting Medium", Fifteenth Symposium (International) on Combustion, The Combustion Institute, Pittsburgh, Pa., pp. 87-100, 1975.
7. Garris, C. A., Toong, T. Y. and Patureau, J.-P., "Chemi-Acoustic Instability Structure in Irreversibly Reacting Systems", presented at the Fifth International Colloquium on Gasdynamics of Explosions and Reactive Systems, University of Orléans, Bourges, France, September 8-10, 1975. Acta Astronautica, 2, pp. 981-997, 1975.
8. Patureau, J.-P., "Acoustic-Kinetic Interactions in Non-Equilibrium H_2-Cl_2 Reactions", Sc.D. Thesis, Department of Mechanical Engineering, M.I.T., January, 1976.
9. Patureau, J.-P., Toong, T. Y. and Garris, C. A., "Experimental Investigation of Acoustic-Kinetic Interactions in Non-Equilibrium H_2-Cl_2 Reactions", Sixteenth Symposium (International) on Combustion, The Combustion Institute, Pittsburgh, Pa., pp. 929-938, 1977.
10. Abouseif, G. E., Ph.D. Thesis, Department of Aeronautics and Astronautics, M.I.T., 1979.
11. Abouseif, G. E., Toong, T. Y. and Converti, J., "Acoustic- and Shock-Kinetic Interactions in Non-Equilibrium H_2-Cl_2 Reactions", Seventeenth Symposium (International) on Combustion, The Combustion Institute, Pittsburgh, Pa., pp. 1341-1351, 1979.
12. Abouseif, G. E. and Toong, T. Y., "Non-Linear Wave-Kinetic Interactions in Non-Equilibrium Exothermic Reactions", Journal of Fluid Mechanics, 103, 1981, pp. 1-22.

13. Abouseif, G. E. and Toong, T. Y., "On Direct Initiation of Gaseous Detonations", *Combustion and Flame*, 45, 1982, pp. 39-46.
14. Abouseif, G. E. and Toong, T. Y., "Theory of Unstable One-Dimensional Detonations", *Combustion and Flame*, 45, 1982, pp. 67-94.
15. Keklak, J. A., "A Low-Frequency Instability Mechanism in a Coaxial Dump Combustor", S.M. Thesis, Mechanical Engineering Department, Mass. Inst. of Tech., January, 1982.
16. Greiner, M., "Onset of Instability in a Chemically Reacting Laminar Shear Layer", S.M. Thesis, Mechanical Engineering Department, Mass. Inst. of Tech., May, 1982.
17. Abouseif, G. E., Keklak, J. A., and Toong, T. Y., "Ramjet Rumble: The Low-Frequency Instability Mechanism in Coaxial Dump Combustors", in preparation.
18. Abouseif, G. E. and Toong, T. Y., "Theory of Unstable Two-Dimensional Detonations: Genesis of Transverse Waves", in preparation.